

WM - PRC

WALL MOUNT PROCESS CONTROLLER

This controller is suited to a wide variety of process applications. It comes in a convenient, wall mountable enclosure for hassle-free installation.

Input signal Current (0/4-20mA)
Voltage (0-10V)

Excitation 24V DC (50mA max)

Resolution 16-bit

Sampling rate 10Hz

Accuracy 0.05%

Temp drift Typically 50ppm/°C

Relay outputs 8 x 5A form A

OPTIONAL

Analog output Isolated 16-bit 4-20 mA or 0-10V output

Serial port Isolated RS232/485



- 5 buttons, 4 status LED's
- High-res LCD display with green backlight, 2 x 16 digits
- Transparent dust cover (not shown in image)
- IP65 dust and splash-proof
- Wall mountable case - 185 x 235 x 119mm (H x W x D)

CODE	DESCRIPTION	POWER*
WM - PRC - R8 - HV	8 x relays	HV
WM - PRC - R8 - LV	8 x relays	LV
WM - PRC - R8A - HV	8 x relays, 1 x analog output	HV
WM - PRC - R8A - LV	8 x relays, 1 x analog output	LV
WM - PRC - R8S - HV	8 x relays, 1 x serial port	HV
WM - PRC - R8S - LV	8 x relays, 1 x serial port	LV
WM - PRC - R8AS - HV	8 x relays, 1 x analog output, 1 x serial port	HV
WM - PRC - R8AS - LV	8 x relays, 1 x analog output, 1 x serial port	LV

* Power supply: **HV** (85-265V AC / 95-370V DC), **LV** (15-48V AC / 10-72V DC)